


911 Dialer – Installation & Programming Instructions

Model 3232GHQ-911

Congratulations on your purchase of a 911 Blocker Model 3232GHQ-911.



Installation:

To install your [911 dialer](#), please use the diagram shown above as reference, and follow these 4 steps:

- 1) Unplug the existing telephone cable from your existing phone.
- 2) Plug this cable into the LINE port of the 911 Dialer.
- 3) Plug one end of the new telephone cable (e.g. patch cord included with your 911 Dialer) in the TEL1 or TEL2 of the 911 Dialer.
- 4) Plug the other end to the existing phone socket (same place where you removed the existing cable in step1).
Done!

Programming:

Note: Your 911 Dialer has been pre-programmed to auto dial 911 at the factory.

Follow the instructions below only if you wish to re-program your 911 Dialer.

1. Lift off the handset to hear dialtone.
2. Enter: ******* wait to hear 'BEEP' — log in the system.
IMPORTANT: You must start entering the above sequence within 1-2 seconds after hearing dialtone.
3. ****9**** wait to hear 'BEEP' — wait to hear 'BEEP' — enters setup mode.
4. ***9*1**200*N**** — wait to hear 'BEEP' — enter phone number to be auto dial where N is any digit 0-9, #
5. ****278*** — wait to hear 'BEEP' — enables auto dialing mode.
6. ****235*** — wait to hear 'BEEP' — enables auto dialing mode.

Note (1): actual commands are in bold. The rest of the letters above are comments.

Note (2): You need to start inputting the digits using a dial-pad of your analog phone **within 1 second** from lifting up the handset. Otherwise, the dialer will automatically dial the number in stored.

REMOTE RE-PROGRAMMING:

You can remotely program your dialer by calling in the phone line where the dialer is installed from another phone e.g. cell phone.

When you dial the number, wait 2 rings before picking up the handset where the Dialer is installed, then enter:

***#1234** wait to hear 'BEEP' — log in the system*.

At this time, follow steps 1-5 above to re-program your 911 Dialer.

Note: You will need someone to pick-up the handset where the dialer is installed at the other end in order to program it remotely. Then, call the phone number where the dialer is installed, and follow the RESET instructions, and then the PROGRAMMING instructions.

For additional support programming your [911 dialer](#), please visit hqtelecom.com